

# **MSDS** simplube SL01

Tribol GR CLS 2

Dear simalube Customer,

EN

We hereby confirm that the automatic lubricators simulube and simulube multipoint with the designation SLO1 are filled with Castrol Tribol GR CLS 2 lubricant. The Material Safety Data Sheet (MSDS) for this lubricant is provided on the following pages. Please visit <a href="www.simatec.com">www.simatec.com</a> for further technical data regarding this lubricant and simatec automatic lubricators.

Werter simalube Kunde

DE

**FR** 

Wir bestätigen hiermit, dass die automatischen Schmierstoffspender simalube und simalube multipoint, mit der Bezeichnung SLO1, mit dem Schmierstoff Castrol Tribol GR CLS 2 befüllt sind. Das Sicherheitsdatenblatt zu diesem Schmierstoff finden Sie auf den folgenden Seiten. Technische Daten zum Schmierstoff und den automatischen Schmierstoffspendern simalube finden Sie unter: www.simatec.com

Cher client simalube

Nous certifions que les graisseurs automatiques simalube et simalube multipoint appelés SL01 sont remplis avec le lubrifiant Castrol Tribol GR CLS 2. La fiche de données de sécurité de ce lubrifiant peut être trouvé dans les pages suivantes. Concernant les données techniques du lubrifiant tout comme les graisseurs automatiques simalube, vous allez trouver ces détails sous le lien suivant : www.simatec.com

#### Estimado cliente de simalube

ES

Por la presente certificamos que los lubricadores automáticos simalube y simalube multipoint con la designación SLO1, están rellenados con el lubricante Castrol Tribol GR CLS 2. La ficha de datos de seguridad de este lubricante Usted pueden encontrar en las siguientes páginas. Para especificaciones técnicas del lubricante y de los lubricadores automáticos simalube ver: <a href="https://www.simatec.com">www.simatec.com</a>

Caro cliente simalube

Con la presente confermiamo che i lubrificatori automatici simalube e simalube multipoint con la designazione SLO1 sono riempiti con lubrificante Castrol Tribol GR CLS 2. La scheda dati di sicurezza per questo lubrificante é riportato sulle seguenti pagine. I dati tecnici del lubrificante e dei lubrificatori automatici sono disponibili sul sito: <a href="https://www.simatec.com">www.simatec.com</a>

08.10.2021 / simatec ag, Wangen a. Aare, Switzerland

© simatec 08.10.21 MSDS - simalube SL01

# **SAFETY DATA SHEET**



# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

 Product code
 468712-DE03

 SDS no.
 468712

 Historic SDS no.
 66460-AG

 Product type
 Grease.

# 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** 

General use of lubricants and greases in vehicles or machinery-Industrial General use of lubricants and greases in vehicles or machinery-Professional

Use of the substance/

Grease for industrial applications

mixture

For specific application advice see appropriate Technical Data Sheet or consult our company

representative.

1.3 Details of the supplier of the safety data sheet

Supplier Castrol (UK) Limited

PO Box 352, Chertsey Road, Sunbury On Thames,

Middlesex,

TW16 9AW Orders/Enquiries: 0845 9645111 Technical Enquiries: 0845 9000209

E-mail address MSDSadvice@bp.com

1.4 Emergency telephone number

**EMERGENCY** Carechem: +44 (0) 1235 239 670 (24/7)

**TELEPHONE NUMBER** 

# **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Product definition Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Eye Irrit. 2, H319

See Section 16 for the full text of the H statements declared above.

See sections 11 and 12 for more detailed information on health effects and symptoms and environmental hazards.

2.2 Label elements

**UFI:** FKM0-K04J-300X-N5VY

**Hazard pictograms** 

**(!)** 

Signal word Warning

**Hazard statements** H319 - Causes serious eye irritation.

**Precautionary statements** 

**Prevention** P280 - Wear eye or face protection.

P264 - Wash hands thoroughly after handling.

Product name Tribol GR CLS 2 Product code 468712-DE03 Page: 1/15

Version 5 Date of issue 8 October 2021 Format United Language ENGLISH

Kingdom (UK)

(United Kingdom)

# **SECTION 2: Hazards identification**

Response P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical attention.

StorageNot applicable.DisposalNot applicable.Supplemental labelNot applicable.

elements

# EU Regulation (EC) No. 1907/2006 (REACH)

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

#### Special packaging requirements

Containers to be fitted with child-resistant fastenings

Not applicable.

Not applicable.

Tactile warning of danger Not applicable.

2.3 Other hazards

Results of PBT and vPvB

assessment

Product does not meet the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006,

Annex XIII.

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do Defatting to the skin.

not result in classification Note: High Pressure Applications

Injections through the skin resulting from contact with the product at high pressure constitute a

major medical emergency.

See 'Notes to physician' under First-Aid Measures, Section 4 of this Safety Data Sheet.

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Product definition Mixture

Highly refined mineral oil and additives. Thickening agent.

Product/ingredient Identifiers % Regulation (EC) No. Type name 1272/2008 [CLP]

palcium dihydroxide REACH #: 01-2119475151-45 <3 Skin Irrit. 2, H315 [1] [2]

EC: 215-137-3 Eye Dam. 1, H318 CAS: 1305-62-0 STOT SE 3, H335

See Section 16 for the full text of the H statements declared above.

<u>Type</u>

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

[6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

# **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

Date of previous issue

Eye contact In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids

should be held away from the eyeball to ensure thorough rinsing. Check for and remove any

contact lenses. Get medical attention.

**Skin contact** Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove

contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before

reuse. Get medical attention if irritation develops.

Product name Tribol GR CLS 2 Product code 468712-DE03 Page: 2/15

Version 5 Date of issue 8 October 2021 Format United Language ENGLISH

Kingdom (UK)

17 January 2020. (United Kingdom)

# **SECTION 4: First aid measures**

Inhalation If inhaled, remove to fresh air. Get medical attention if symptoms occur.

**Ingestion** Do not induce vomiting unless directed to do so by medical personnel. Never give anything by

mouth to an unconscious person. If unconscious, place in recovery position and get medical

attention immediately. Get medical attention if symptoms occur.

Protection of first-aiders No action shall be taken involving any personal risk or without suitable training. It may be

dangerous to the person providing aid to give mouth-to-mouth resuscitation.

#### 4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

#### Potential acute health effects

**Skin contact** Defatting to the skin. May cause skin dryness and irritation.

**Eye contact** Causes serious eye irritation.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Inhalation** Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.

**Ingestion** Ingestion of large quantities may cause nausea and diarrhoea.

**Eye contact** Potential risk of transient stinging or redness if accidental eye contact occurs.

#### 4.3 Indication of any immediate medical attention and special treatment needed

**Notes to physician**Treatment should in general be symptomatic and directed to relieving any effects.

Note: High Pressure Applications

Injections through the skin resulting from contact with the product at high pressure constitute a major medical emergency. Injuries may not appear serious at first but within a few hours tissue becomes swollen, discoloured and extremely painful with extensive subcutaneous necrosis. Surgical exploration should be undertaken without delay. Thorough and extensive debridement of the wound and underlying tissue is necessary to minimise tissue loss and prevent or limit permanent damage. Note that high pressure may force the product considerable distances

along tissue planes.

# **SECTION 5: Firefighting measures**

## 5.1 Extinguishing media

Suitable extinguishing

media

In case of fire, use water fog, alcohol resistant foam, dry chemical or carbon dioxide

extinguisher or spray.

Unsuitable extinguishing

media

Do not use water jet. The use of a water jet may cause the fire to spread by splashing the

burning product.

# 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

No specific fire or explosion hazard.

**Hazardous combustion** 

products

Combustion products may include the following:

carbon oxides (CO, CO<sub>2</sub>) (carbon monoxide, carbon dioxide)

metal oxide/oxides

#### 5.3 Advice for firefighters

Special precautions for fire-fighters

Special protective equipment for fire-fighters

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

# **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Floors may be slippery; use care to avoid falling. Provide adequate ventilation. Put on appropriate personal protective equipment.

Product name Tribol GR CLS 2 Product code 468712-DE03 Page: 3/15

Version 5 Date of issue 8 October 2021 Format United Language ENGLISH

Kingdom (UK)

(United Kingdom)

#### **SECTION 6: Accidental release measures**

For emergency responders

F specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### 6.3 Methods and material for containment and cleaning up

**Small spill** 

Move containers from spill area. Vacuum or sweep up material and place in a designated, labelled waste container. Dispose of via a licensed waste disposal contractor.

Large spill

Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labelled waste container. Avoid creating dusty conditions and prevent wind dispersal. If emergency personnel are unavailable, contain spilt material. Suction or scoop the spill into appropriate disposal or recycling vessels, then cover spill area with oil absorbent. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other sections

See Section 1 for emergency contact information.

See Section 5 for firefighting measures.

See Section 8 for information on appropriate personal protective equipment.

See Section 12 for environmental precautions.

See Section 13 for additional waste treatment information.

# **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 7.1 Precautions for safe handling

**Protective measures** 

Put on appropriate personal protective equipment. Do not ingest. Avoid contact with eyes, skin and clothing. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Do not reuse container. Empty containers retain product residue and can be hazardous.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store and use only in equipment/containers designed for use with this product. Do not store in unlabelled containers.

#### 7.3 Specific end use(s)

Recommendations

See section 1.2 and Exposure scenarios in annex, if applicable.

# **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

#### 8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

alcium dihydroxide

EH40/2005 WELs (United Kingdom (UK)).

TWA: 1 mg/m³ 8 hours. Issued/Revised: 8/2018 Form: Respirable

fraction

STEL: 4 mg/m³ 15 minutes. Issued/Revised: 8/2018 Form: Respirable

fraction

TWA: 5 mg/m<sup>3</sup> 8 hours. Issued/Revised: 1/1997

Whilst specific OELs for certain components may be shown in this section, other components may be present in any mist, vapour or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

Product name Tribol GR CLS 2 Product code 468712-DE03 Page: 4/15

Version 5 Date of issue 8 October 2021 Format United Language ENGLISH

Kingdom (UK)

(United Kingdom)

# **SECTION 8: Exposure controls/personal protection**

# Recommended monitoring procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### **Derived No Effect Level**

Product/ingredient name	Type		Exposure	Value	Population	Effects
calcium hydroxide		Long term Inhalation	-	1 mg/m³	Workers	Systemic
	DNEL	Short term Inhalation	-	4 mg/m³	Workers	Local
	DNEL	Short term Inhalation	-	4 mg/m³	Workers	Systemic

#### **Predicted No Effect Concentration**

No PNECs available

#### 8.2 Exposure controls

# Appropriate engineering controls

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

# **Individual protection measures**

#### **Hygiene measures**

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.

# **Respiratory protection**

In case of insufficient ventilation, wear suitable respiratory equipment.

For protection against metal working fluids, respiratory protection that is classified as "resistant to oil" (class R) or oil proof (class P) should be selected where appropriate. Depending on the level of airborne contaminants, an air-purifying, half-mask respirator (with HEPA filter) including disposable (P- or R-series) (for oil mists less than 50mg/m3), or any powered, air-purifying respirator equipped with hood or helmet and HEPA filter (for oil mists less than 125 mg/m3). Where organic vapours are a potential hazard during metalworking operations, a combination particulate and organic vapour filter may be necessary.

The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

# Eye/face protection Skin protection Hand protection

Safety glasses with side shields.

## **General Information:**

Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. The correct choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. Most gloves provide protection for only a limited time before they must be discarded and replaced (even the best chemically resistant gloves will break down after repeated chemical exposures).

Gloves should be chosen in consultation with the supplier / manufacturer and taking account of a full assessment of the working conditions.

Recommended: Nitrile gloves.

Product name Tribol GR CLS 2

Product code 468712-DE03

Page: 5/15

Page: 5/15

Product code 468712-DE03

Page: 5/15

Product code 468712-DE03

Page: 5/15

Format Kingdom (UK)

(UK)

Date of previous issue 17 January 2020.

United Kingdom)

# **SECTION 8: Exposure controls/personal protection**

#### Breakthrough time:

Breakthrough time data are generated by glove manufacturers under laboratory test conditions and represent how long a glove can be expected to provide effective permeation resistance. It is important when following breakthrough time recommendations that actual workplace conditions are taken into account. Always consult with your glove supplier for up-to-date technical information on breakthrough times for the recommended glove type. Our recommendations on the selection of gloves are as follows:

#### Continuous contact:

Gloves with a minimum breakthrough time of 240 minutes, or >480 minutes if suitable gloves can be obtained.

If suitable gloves are not available to offer that level of protection, gloves with shorter breakthrough times may be acceptable as long as appropriate glove maintenance and replacement regimes are determined and adhered to.

Short-term / splash protection:

Recommended breakthrough times as above.

It is recognised that for short-term, transient exposures, gloves with shorter breakthrough times may commonly be used. Therefore, appropriate maintenance and replacement regimes must be determined and rigorously followed.

#### **Glove Thickness:**

For general applications, we recommend gloves with a thickness typically greater than 0.35 mm.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times. Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

- Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
- Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential.

# Skin and body

Use of protective clothing is good industrial practice.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

#### Refer to standards:

Respiratory protection: EN 529 Gloves: EN 420, EN 374 Eye protection: EN 166 Filtering half-mask: EN 149

Filtering half-mask with valve: EN 405 Half-mask: EN 140 plus filter Full-face mask: EN 136 plus filter

Particulate filters: EN 143
Gas/combined filters: EN 14387

# **Environmental exposure** controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Product name Tribol GR CLS 2 Product code 468712-DE03 Page: 6/15

Version 5 Date of issue 8 October 2021 Format United Language ENGLISH

Kingdom (UK) (United Kingdom)

# SECTION 9: Physical and chemical properties

# 9.1 Information on basic physical and chemical properties

**Appearance** 

**Physical state** Grease. Colour Beige. Not available. Odour Not available. **Odour threshold** Not applicable. pН Not available. Melting point/freezing point Not available. Initial boiling point and boiling

range

>130 °C **Drop Point** 

Flash point Closed cup: 212°C (413.6°F) [Estimated. Based on Lubricants - Base Oils]

**Evaporation rate** Not available. Flammability (solid, gas) Not available. Upper/lower flammability or Not available.

explosive limits

Not available. Vapour pressure Vapour density Not available. Relative density Not available.

<1000 kg/m3 (<1 g/cm3) at 20°C Density

Solubility(ies) insoluble in water. Partition coefficient: n-octanol/ Not available.

water

**Auto-ignition temperature** Not available. **Decomposition temperature** Not available. Not available. **Viscosity Explosive properties** Not available. **Oxidising properties** Not available.

#### 9.2 Other information

No additional information.

# SECTION 10: Stability and reactivity

No specific test data available for this product. Refer to Conditions to avoid and Incompatible 10.1 Reactivity

materials for additional information.

10.2 Chemical stability The product is stable.

10.3 Possibility of Under normal conditions of storage and use, hazardous reactions will not occur. hazardous reactions Under normal conditions of storage and use, hazardous polymerisation will not occur.

10.4 Conditions to avoid Avoid all possible sources of ignition (spark or flame).

10.5 Incompatible materials Reactive or incompatible with the following materials: oxidising materials.

10.6 Hazardous Under normal conditions of storage and use, hazardous decomposition products should not be decomposition products produced.

# **SECTION 11: Toxicological information**

# 11.1 Information on toxicological effects

**Acute toxicity estimates** 

Not available.

Information on likely routes of exposure

Routes of entry anticipated: Dermal, Inhalation.

Potential acute health effects

Inhalation No known significant effects or critical hazards

Product name Tribol GR CLS 2 Product code 468712-DE03 Page: 7/15

Version 5 Date of issue 8 October 2021 **Format United** Language ENGLISH

> **Kingdom** (UK)

(United Kingdom) Date of previous issue 17 January 2020

# **SECTION 11: Toxicological information**

**Ingestion** No known significant effects or critical hazards.

**Skin contact** Defatting to the skin. May cause skin dryness and irritation.

**Eve contact** Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

InhalationNo specific data.IngestionNo specific data.

**Skin contact** Adverse symptoms may include the following:

irritation dryness cracking

**Eye contact** Adverse symptoms may include the following:

pain or irritation watering redness

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Inhalation** Inhalation of oil mist or vapours at elevated temperatures may cause respiratory irritation.

**Ingestion** Ingestion of large quantities may cause nausea and diarrhoea.

Eye contact Potential risk of transient stinging or redness if accidental eye contact occurs.

## Potential chronic health effects

GeneralNo known significant effects or critical hazards.CarcinogenicityNo known significant effects or critical hazards.MutagenicityNo known significant effects or critical hazards.Developmental effectsNo known significant effects or critical hazards.Fertility effectsNo known significant effects or critical hazards.

# **SECTION 12: Ecological information**

#### 12.1 Toxicity

Environmental hazards Not classified as dangerous

#### 12.2 Persistence and degradability

Not expected to be rapidly degradable.

#### 12.3 Bioaccumulative potential

Not available.

12.4 Mobility in soil

Soil/water partition Not available.

coefficient (Koc)

Mobility Grease. insoluble in water.

# 12.5 Results of PBT and vPvB assessment

Product does not meet the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII.

**12.6 Other adverse effects** No known significant effects or critical hazards.

# SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

## 13.1 Waste treatment methods

**Product** 

Methods of disposal Where possible, arrange for product to be recycled. Dispose of via an authorised person/

licensed waste disposal contractor in accordance with local regulations.

Hazardous waste Yes

<u>European waste catalogue (EWC)</u>

Waste code	Waste designation
12 01 12*	spent waxes and fats

Product name Tribol GR CLS 2 Product code 468712-DE03 Page: 8/15

Version 5 Date of issue 8 October 2021 Format United Language ENGLISH

Kingdom (UK)

(United Kingdom)

# **SECTION 13: Disposal considerations**

However, deviation from the intended use and/or the presence of any potential contaminants may require an alternative waste disposal code to be assigned by the end user.

#### **Packaging**

Methods of disposal Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.

Waste code	European waste catalogue (EWC)
15 01 10*	packaging containing residues of or contaminated by hazardous substances
Special precautions	This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

References Commission 2014/955/EU Directive 2008/98/EC

# **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

14.6 Special precautions for

Not available.

14.7 Transport in bulk according to IMO instruments

Not available.

# SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

**Annex XIV** 

None of the components are listed.

Substances of very high concern

None of the components are listed.

EU Regulation (EC) No. 1907/2006 (REACH)

**Annex XVII - Restrictions** 

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Not applicable.

**Other regulations** 

**REACH Status** The company, as identified in Section 1, sells this product in the EU in compliance with the current requirements of REACH.

Product name Tribol GR CLS 2 Product code 468712-DE03 Page: 9/15

Version 5 Date of issue 8 October 2021 **Format United** Language ENGLISH

**Kingdom** (UK) (United Kingdom)

# **SECTION 15: Regulatory information**

**United States inventory** 

(TSCA 8b)

All components are active or exempted.

Australia inventory (AICS) All components are listed or exempted.

Canada inventory At least one component is not listed in DSL but all such components are listed in NDSL.

China inventory (IECSC)

Japan inventory (ENCS)

Korea inventory (KECI)

Philippines inventory

At least one component is not listed.

All components are listed or exempted.

At least one component is not listed.

(PICCS)

Taiwan Chemical Substances Inventory All components are listed or exempted.

(TCSI)

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

EU - Water framework directive - Priority substances

None of the components are listed.

**Seveso Directive** 

This product is not controlled under the Seveso Directive.

15.2 Chemical safety

assessment

A Chemical Safety Assessment has been carried out for one or more of the substances within this mixture. A Chemical Safety Assessment has not been carried out for the mixture itself.

# **SECTION 16: Other information**

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by

Road

ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment CSR = Chemical Safety Report DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978. ("Marpol" = marine pollution)
OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation

[Regulation (EC) No. 1907/2006]

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SADT = Self-Accelerating Decomposition Temperature

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

Product name Tribol GR CLS 2 Product code 468712-DE03 Page: 10/15

Version 5 Date of issue 8 October 2021 Format United Language ENGLISH

Kingdom (UK)

(United Kingdom)

# **SECTION 16: Other information**

UVCB = Complex hydrocarbon substance

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Varies = may contain one or more of the following 64741-88-4 / RRN 01-2119488706-23, 64741-89-5 / RRN 01-2119487067-30, 64741-95-3 / RRN 01-2119487081-40, 64741-96-4/ RRN

01-2119483621-38, 64742-01-4 / RRN 01-2119488707-21, 64742-44-5 / RRN

01-2119985177-24, 64742-45-6, 64742-52-5 / RRN 01-2119467170-45, 64742-53-6 / RRN

01-2119480375-34, 64742-54-7 / RRN 01-2119484627-25, 64742-55-8 / RRN

01-2119487077-29, 64742-56-9 / RRN 01-2119480132-48, 64742-57-0 / RRN

01-2119489287-22, 64742-58-1, 64742-62-7 / RRN 01-2119480472-38, 64742-63-8, 64742-65-0 / RRN 01-2119471299-27, 64742-70-7 / RRN 01-2119487080-42, 72623-85-9 /

RRN 01-2119555262-43, 72623-86-0 / RRN 01-2119474878-16, 72623-87-1 / RRN

01-2119474889-13

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification  Eye Irrit. 2, H319		Justification	
		Calculation method	
Full text of abbreviated H statements	H315 H318 H335	Causes skin irritation. Causes serious eye damage. May cause respiratory irritation.	
Full text of classifications [CLP/GHS]	Eye Dam. 1 Skin Irrit. 2 STOT SE 3	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1 SKIN CORROSION/IRRITATION - Category 2 SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3	
<u>History</u>			
Date of issue/ Date of revision	08/10/2021.		
Date of previous issue	17/01/2020.		
Prepared by	Product Stewardship		

▼ Indicates information that has changed from previously issued version.

#### **Notice to reader**

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

 Product name
 Tribol GR CLS 2
 Product code
 468712-DE03
 Page: 11/15

 Version 5
 Date of issue 8 October 2021
 Format Kingdom (UK)
 United Kingdom (UK)
 Language
 ENGLISH

Date of previous issue 17 January 2020. (United Kingdom)



# Annex to the extended Safety Data Sheet (eSDS)

Industrial

## Identification of the substance or mixture

Product definition Mixture

Code 468712-DE03

Product name Tribol GR CLS 2

**Section 1: Title** 

Short title of the exposure

List of use descriptors

scenario

General use of lubricants and greases in vehicles or machinery - Industrial

Identified use name: General use of lubricants and greases in vehicles or

machinery-Industrial

Process Category: PROC01, PROC02, PROC08b, PROC09

Sector of end use: SU03

Subsequent service life relevant for that use: No. Environmental Release Category: ERC04, ERC07

Specific Environmental Release Category: ATIEL-ATC SPERC 4.Biv1

Processes and activities covered by the exposure

scenario

Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.

# Section 2 Operational conditions and risk management measures

# Section 2.1 Control of worker exposure

**Product characteristics:** 

Physical state: Liquid, vapour pressure < 0.5 kPa

Concentration of substance in product: Covers use of substance/product up to 100 % (unless stated

differently)

Frequency and duration of use: Covers daily exposures up to 8 hours

Other conditions affecting workers exposure: Assumes use at not more than 20°C above ambient temperature.

Assumes a good basic standard of occupational hygiene is

implemented

# Contributing scenarios: Operational conditions and risk management measures

General measures applicable to all activities:

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN 374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop. Avoid direct eye contact with product also via contamination on hands.

General exposures (closed systems): No other specific measures identified.

Initial factory fill of equipment Use in contained systems:

No other specific measures identified.

Initial factory fill of equipment Open systems:

Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Avoid carrying out operation for more than 4 hours.

Operation of equipment containing engine oils and similar Use in contained systems: No other specific measures identified.

Equipment cleaning and maintenance:

Drain down system prior to equipment break-in or maintenance. Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training. Retain drain-downs in sealed storage pending disposal or for subsequent recycle.

Equipment cleaning and maintenance Operation is carried out at elevated temperature (> 20°C above ambient temperature):

Drain down and flush system prior to equipment break-in or maintenance. Provide extract ventilation to emission points when contact with warm (>50°C) lubricant is likely. Wear chemical-resistant gloves (tested to EN374) in

**Tribol GR CLS 2** 

combination with intensive management supervision controls. Retain drain-downs in sealed storage pending disposal or for subsequent recycle.

#### Storage:

Store substance within a closed system.

# Section 2.2: Control of environmental exposure

No exposure scenario is presented because the product is not classified for the Environment

# Section 3: Exposure estimation and reference to its source

Exposure estimation and reference to its source - Environment

**Exposure assessment (environment):**No exposure scenario is presented because the product is not

classified for the Environment

Exposure estimation and reference to its source - Workers

Exposure assessment (human): The ECETOC TRA tool has been used to estimate workplace

exposures unless otherwise indicated.

# Section 4: Guidance to check compliance with the exposure scenario

Section 4. Guidance to check compliance with the exposure scenario			
Environment	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.ATIEL.org/REACH_GES		
Health	Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.		



# Annex to the extended Safety Data Sheet (eSDS)

**Professional** 

## Identification of the substance or mixture

**Product definition** Mixture Code 468712-DE03 **Product name** Tribol GR CLS 2

**Section 1: Title** 

Short title of the exposure

List of use descriptors

scenario

General use of lubricants and greases in vehicles or machinery - Professional

Identified use name: General use of lubricants and greases in vehicles or

machinery-Professional

Process Category: PROC01, PROC02, PROC08a, PROC08b, PROC20

Sector of end use: SU22

Subsequent service life relevant for that use: No. Environmental Release Category: ERC09a, ERC09b

Specific Environmental Release Category: ESVOC SpERC 9.6b.v1

**Processes and activities** covered by the exposure

scenario

Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.

# Section 2 Operational conditions and risk management measures

#### Section 2.1 Control of worker exposure

**Product characteristics:** 

Liquid, vapour pressure < 0.5 kPa **Physical state:** 

Concentration of substance in product: Covers use of substance/product up to 100 % (unless stated

differently)

Frequency and duration of use: Covers daily exposures up to 8 hours

Other conditions affecting workers exposure: Assumes use at not more than 20°C above ambient temperature.

Assumes a good basic standard of occupational hygiene is

implemented

# Contributing scenarios: Operational conditions and risk management measures

General measures applicable to all activities:

Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN 374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop. Use suitable eye protection. Avoid direct eye contact with product also via contamination on hands.

Operation of equipment containing engine oils and similar Use in contained systems: No other specific measures identified.

Material transfers Non-dedicated facility:

Avoid carrying out activities involving exposure for more than 4 hours per day. Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.

Equipment cleaning and maintenance Dedicated facility:

Drain down system prior to equipment break-in or maintenance. Retain drain-downs in sealed storage pending disposal or for subsequent recycle.

Storage:

Store substance within a closed system.

# Section 2.2: Control of environmental exposure

No exposure scenario is presented because the product is not classified for the Environment

# Section 3: Exposure estimation and reference to its source

Exposure estimation and reference to its source - Environment

**Exposure assessment (environment):** No exposure scenario is presented because the product is not

classified for the Environment

**Exposure estimation and reference to its source - Workers** 

**Exposure assessment (human):** The ECETOC TRA tool has been used to estimate workplace

exposures unless otherwise indicated.

# Section 4: Guidance to check compliance with the exposure scenario

	•
Environment	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.ATIEL.org/REACH_GES
Health	Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.