

### **MSDS** simplube SL16

Maschinenoel paraffinbasisch ISO 68

Dear simalube Customer,

**EN** 

We hereby confirm that the automatic lubricators simulube and simulube multipoint with the designation SL16 are filled with Motorex machine oil 68 lubricant. The Material Safety Data Sheet (MSDS) for this lubricant is provided on the following pages. Please visit <a href="www.simatec.com">www.simatec.com</a> for further technical data regarding this lubricant and simatec automatic lubricators.

Werter simalube Kunde

DE

Wir bestätigen hiermit, dass die automatischen Schmierstoffspender simalube und simalube multipoint, mit der Bezeichnung SL16, mit dem Schmierstoff Motorex machine oil 68 befüllt sind. Das Sicherheitsdatenblatt zu diesem Schmierstoff finden Sie auf den folgenden Seiten. Technische Daten zum Schmierstoff und den automatischen Schmierstoffspendern simalube finden Sie unter: www.simatec.com

Cher client simalube

FR

Nous certifions que les graisseurs automatiques simalube et simalube multipoint appelés SL16 sont remplis avec le lubrifiant Motorex machine oil 68. La fiche de données de sécurité de ce lubrifiant peut être trouvé dans les pages suivantes. Concernant les données techniques du lubrifiant tout comme les graisseurs automatiques simalube, vous allez trouver ces détails sous le lien suivant : www.simatec.com

#### Estimado cliente de simalube

ES

Por la presente certificamos que los lubricadores automáticos simalube y simalube multipoint con la designación SL16, están rellenados con el lubricante Motorex machine oil 68. La ficha de datos de seguridad de este lubricante Usted pueden encontrar en las siguientes páginas. Para especificaciones técnicas del lubricante y de los lubricadores automáticos simalube ver: www.simatec.com

Caro cliente simalube

IT

Con la presente confermiamo che i lubrificatori automatici simalube e simalube multipoint con la designazione SL16 sono riempiti con lubrificante Motorex machine oil 68. La scheda dati di sicurezza per questo lubrificante é riportato sulle seguenti pagine. I dati tecnici del lubrificante e dei lubrificatori automatici sono disponibili sul sito: <a href="https://www.simatec.com">www.simatec.com</a>

03.04.2018 / simatec ag, Wangen a. Aare, Switzerland

© simatec 03.04.18 MSDS - simalube SL16

Revision: 03.04.2018



## Safety data sheet according to (EU) 2015/830

Printing date 03.04.2018

Version number 1.0

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Maschinenoel paraffinbasisch ISO 68
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Lubricating oil Only for proper handling.
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MOTOREX AG LANGENTHAL Schmiertechnik Bern-Zürich-Strasse 31 CH-4901 Langenthal Tel. +41 (0)62 919 74 74

· Only representative in EU:

MOTOREX Deutschland AG, Bismarckstrasse 28, D-69198 Schriesheim

- · Further information obtainable from: msds@motorex.com
- · 1.4 Emergency telephone number:

In case of a medical emergency following exposure to a chemical, the public should call NHS Direct in England or Wales 0845 46 47 or NHS 24 in Scotland 08454 24 24 24 (UK only).

#### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008
  The product is not classified, according to the CLP regulation.
- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

#### SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 64742-54-7	Distillates (petroleum), hydrotreated heavy	70-100%
EINECS: 265-157-1	paraffinic	
Index number: 649-467-00-8	substance with a Community workplace exposure	
Reg.nr.: 01-2119484627-25	limit	

(Contd. on page 2)

Printing date 03.04.2018

Version number 1.0

Trade name: Maschinenoel paraffinbasisch ISO 68

(Contd. of page 1)

Revision: 03.04.2018

· Additional information:

Note L: The classification as carcinogen does not apply because the mixture (or substance) contains less than 3% dimethyl sulfoxide extract (DMSO), measured according to IP 346. For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information: No special measures required.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Wash with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomitting. Do not take in resorption stimulating agents.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

### SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

Use fire extinguishing methods suitable to surrounding conditions.

- 5.2 Special hazards arising from the substance or mixture Complete combustion will result in carbon dioxide and water.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

#### SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· 6.4 Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

- 7.1 Precautions for safe handling No special measures required.
- Information about fire and explosion protection: Do not heat above flash point.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.

(Contd. on page 3)

Printing date 03.04.2018

Version number 1.0

Trade name: Maschinenoel paraffinbasisch ISO 68

(Contd. of page 2)

Revision: 03.04.2018

· Storage class: 10

· 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

#### 64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinic

WEL Short-term value: 10 mg/m³ Long-term value: 5 mg/m³

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Respiratory protection:

Not necessary if room is well-ventilated.

Respiratory protection if formation of aerosol or mist: use mask with filter type A2, A2/P2 or ABEK.

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Protective gloves to EN374, resistant to oil in use. Standard EN 374 Level 3 control G1 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Fluorocarbon rubber (Viton)

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the mixture of chemicals mentioned below the penetration time has to be at least 60 minutes (Permeation according to EN 374 Part 3: Level 1).

- · Eye protection: Goggles recommended during refilling
- Body protection: Protective work clothing

### SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Colour: Fluid

Yellow - Brown

· Odour:

weak

(Contd. on page 4)

Revision: 03.04.2018

# Safety data sheet according to (EU) 2015/830

Printing date 03.04.2018

Version number 1.0

Trade name: Maschinenoel paraffinbasisch ISO 68

	(Contd. of pag
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition Melting point/freezing point: Initial boiling point and boiling range	Undetermined. : Undetermined.
Flash point:	>200 °C
Flammability (solid, gas):	Not applicable.
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard
Explosion limits: Lower: Upper:	Not determined. Not determined.
Vapour pressure:	Not determined.
Density at 20 °C: Relative density Vapour density Evaporation rate	0.875 g/cm³ (ASTM D 4052) Not determined. Not determined. Not determined.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity: Dynamic: Kinematic:	Not determined. 68mm²/s @40 °C (DIN 51562-1)
Solids content: 9.2 Other information	0.0 % No further relevant information available.

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinicOralLD505,000 mg/kg (rat)	· LD/LC50	values rele	evant for classification:		
Oral LD50 5,000 mg/kg (rat)	64742-54-	-7 Distillate	es (petroleum), hydrotreated heavy paraffinic		
	Oral	LD50	5,000 mg/kg (rat)		

(Contd. on page 5)

Revision: 03.04.2018

## Safety data sheet according to (EU) 2015/830

Printing date 03.04.2018

Version number 1.0

Trade name: Maschinenoel paraffinbasisch ISO 68

			(Contd. of page 4)
	LOAEL	125 mg/kg/24h (rat)	
Derm	al LD50	2,000-5,000 mg/kg (rabbit)	
	NOAEL	150 mg/kg/24h (mouse)	
		30-2,000 mg/kg/24h (rat)	
		1,000 mg/kg/24h (rabbit)	
	LOAEL	100 mg/kg/24h (mouse)	
Inhala	ative LC50 / 4h	2.18-5.53 mg/l (rat)	
	NOEL	220 mg/m3 (rat)	
	NOAEL	980 mg/m3 (rat)	

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Based on available data, the classification criteria are not met.

· Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

· 12.1 Toxicity

· Aqua	tic toxicity:
64742	2-54-7 Distillates (petroleum), hydrotreated heavy paraffinic
LL50	10,000 mg/l/96h (aquatic invertebrates)
	100 mg/l/96h (fish)
LL50	10,000 mg/l/72h (aquatic invertebrates)
LL50	10,000 mg/l/48h (aquatic invertebrates)
LL50	10,000 mg/l/24h (aquatic invertebrates)
EL50	10,000 mg/l/48h (aquatic invertebrates)

· 12.2 Persistence and degradability No further relevant information available.

### · 12.3 Bioaccumulative potential

#### 64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinic

Partition coefficient | >6 [---] (log Kow) (Bioaccumulation)

- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (according to Appendix 1 AwSV): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

(Contd. on page 6)

Printing date 03.04.2018

Version number 1.0

Trade name: Maschinenoel paraffinbasisch ISO 68

(Contd. of page 5)

Revision: 03.04.2018

· 12.6 Other adverse effects No further relevant information available.

### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact waste processors for recycling information.

· European waste catalogue

12 01 07\* mineral-based machining oils free of halogens (except emulsions and solutions)

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number ADR/RID/ADN, ADN, IMDG, IATA	Void	
14.2 UN proper shipping name ADR/RID/ADN, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR/RID/ADN, ADN, IMDG, IATA Class	Void	
14.4 Packing group ADR/RID/ADN, IMDG, IATA	Void	
14.5 Environmental hazards: Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
14.7 Transport in bulk according to Ai II of Marpol and the IBC Code	nnex Not applicable.	
UN "Model Regulation":	Void	

### **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 7)

Printing date 03.04.2018

Version number 1.0

Revision: 03.04.2018

Trade name: Maschinenoel paraffinbasisch ISO 68

(Contd. of page 6)

The classification of the mixture was carried out by calculation in accordance with the rules laid down in Annex I of Regulation (EC) No 1272/2008.

No special training instructions to ensure protection of human health and environment are required.

· Department issuing SDS: Abteilung Produktsicherheit

GB -